

# Smart Tube CH1357 Series

## T8 Series Linear LED Tube



### Product Description

The CH1357 smart T8 LED tubes can work on both ballast compatible and EM&Mains applications. In ballast compatible model it can work with both electrical and inductance ballast, while in EM&Mains model it works directly in the line voltage 176-264V. One lamp with two functions, you don't need to have inventory for two lamps, which will decrease your inventory cost much.

### Tube Features

- \* Both ballast compatible model and EM&Mains model, two functions in one lamp, with same lumen output
- \* Ballast compatible for most electronic ballasts
- \* High Efficacy: More than 100 LPM with ballast included
- \* Safe explosion-proof cover
- \* High transmittance



Intertek

International Application No.:PCT/CN2016/079652  
Patent No. in China:2015106846583/201520815855X/2015206665935  
Patent No.in Europe:EP3024303A2

### Product Specification

Product	EM&Mains Power (W)	Compatible Power (W)	Luemn (lm)	CCT (K)	CRI	Lifetime (hrs)	Socket	Dimension (mm)	Beam Angle(°)	Operation Mode
CH1357	20	22	2200	3000/4000/6500	83	50000	G13	Φ26×1200	160°	Compatible & EM&Mains
CH1357	24	27	2600	3000/4000/6500	83	50000	G13	Φ26×1500	160°	Compatible & EM&Mains



europa@chlighting.com