

Wall&Ceiling Light


Base and frame: nylon reinforced fiberglass.
With silicon gasket at a waterproof IP55

Reflector: pressed aluminum.
Diffuser: opal polycarbonate.
Wiring: included 100V-240V 50Hz power supply, fasten connector.
Double insulated.
Application: ceiling&wall,both indoor and outdoor use.
Color:white,black,grey

Walt



LED



walt.w



Base and frame: polycarbonate.fix with pitch
Waterproof IP44
Diffuser: opal polycarbonate.
Install bulb: E27 CFL or 2D fluorescent tube.
Application: ceiling, both indoor and outdoor use.
Color:white,silver,golden

walt.a LED



Base and frame: die casting aluminum
Waterproof IP65
Diffuser: opal polycarbonate.
Install bulb:SMD LED,2x E27 CFL ,2D fluorescent tube.
Application: ceiling & wall, outdoor use.
Color:black,grey.

Code	Model	Input Voltage	Bulb	Power	Lumen	Color Temperature	Product Dimension(mm)
io-105001	walt	100-240V AC	SMD LED	10w	700	4000k	D295H90
io-105002	walt	100-240V AC	CFL	20W	1000	2700K/4000K	D295H90
io-105003	walt.w	100-240V AC	CFL	2X20W	2000	2700K/4000K	D325H100
io-105004	walt.w	100-240V AC	2D	28W	2000	2700K/6400K	D325H100
io-105005	walt.a	100-240V AC	SMD LED	30w	2100	4000k	D360H120
io-105006	walt.a	100-240V AC	CFL	2X20W	2000	2700K/4000K	D360H120
io-105007	walt.a	100-240V AC	2D	28w	2000	2700K/6400K	D325H100