

Cabinet Light T5 LED

ALLOTT



Input Voltage:AC85V-264V,
Light Source:3528 SMD LED
Color Temperature: Cool White (6000K-7000K),Natural White (4000K-4500K),WarmWhite(3000K-3500K)
LifeSpan:30,000Hours
View Angle:>120 degree
LED Drive Mode:Constant Current Mode
Shell:PVC Bracket



| Code | Item NO. | LED Power | Luminous Flux | Dimension(mm) | | | Size per carton |
|-----------|----------|-----------|---------------|---------------|------|----|----------------------|
| | | | | a | b | c | |
| io-201012 | AL T4 | 4W | 312(CW) | 318 | 288 | 16 | 463×310×190mm/30pcs |
| io-201013 | AL T7 | 7W | 730(CW) | 579 | 549 | 16 | 650×140×170mm/30pcs |
| io-201014 | AL T11 | 11W | 1100(CW) | 879 | 849 | 16 | 950×140×170mm/30pcs |
| io-201015 | AL T14 | 14W | 1400(CW) | 1179 | 1149 | 16 | 1300×140×170mm/30pcs |
| io-201016 | AL T16 | 16W | 1560(CW) | 1479 | 1449 | 16 | 1600×140×170mm/30pcs |

Cabinet Light T4/T5 Fluorescent

Match lamp:T4/T5
Built-in fuse protection and electronic ballast;
Integral switch,150cm powercord(with plug),transparent cover,reflector;
Linkable design up to 200W;
Material:plastic



Linear4



Linear5



| Code | Lamp | L×W×H(mm) | Packing meas(cm) | Code | Lamp | L×W×H(mm) | Packing meas(cm) |
|-----------|--------|-----------|----------------------|-----------|--------|-------------|----------------------|
| io-201017 | T4 6W | 270×22×45 | 29.5×26.5×34.5/30pcs | io-201023 | T5 6W | 268×22×43 | 53×20.5×28.5/30pcs |
| io-201018 | T4 8W | 390×22×45 | 41.5×26.5×34.5/30pcs | io-201024 | T5 8W | 343×22×43 | 53×20.5×28.5/30pcs |
| io-201019 | T4 12W | 420×22×45 | 44×26.5×34.5/30pcs | io-201025 | T5 13W | 570.5×22×43 | 61.5×20.5×28.5/30pcs |
| io-201020 | T4 16W | 515×22×45 | 54×26.5×34.5/30pcs | io-201026 | T5 14W | 603×22×43 | 64.5×20.5×28.5/30pcs |
| io-201021 | T4 20W | 615×22×45 | 64×26.5×34.5/30pcs | io-201027 | T5 21W | 922×22×43 | 97.5×20.5×19/30pcs |
| io-201022 | T4 24W | 710×22×45 | 74×26.5×34.5/30pcs | io-201028 | T5 28W | 1203×22×43 | 127.5×20.5×19/30pcs |