

## Ceiling Light

### Pessoa LED



These series is intended for replace use to 2x26w classic downlight available in three size With round or square version. It's designed for maximum light output with SMD LED and high efficiency LED driver.


Body: die casting aluminum  
Diffuser: opal polycarbonate.  
Application: ceiling, indoor use.  
Color: white



■ PSS



■ PSR



### Professional version LED



■ PRO-PS

These series is intended for professional use and available in three size. All the armatures are equipped with high quality LED arrays. The design makes it possible for cold air to flow up from the room directly into the cooling element. These armatures are also available with a dimmable driver.

Body: die casting aluminum  
Diffuser: opal polycarbonate.  
Application: ceiling, indoor use.  
Color: black, grey.

### Classic version

#### CFL



■ ECO-PS

This downlight, popular used in home, office, shop. We supply 3 possible choices with different control gear and fasten connector.

Body: aluminum  
Diffuser: tempered glass.  
Bulb: 2X18W CFL(E27) , 2X26W PLC(G24d3, G24q3)  
Application: ceiling, indoor use.  
Color: white, grey, brass.

Code	Model	Voltage (V)	Current (mA)	Power (W)	Flux (lm)	Dimension(mm)		
						Surface Diam.	Hole Diam.	Height
io-203007	PS9R	110-240	99mA	LED9W	420lm	Φ147	Φ135	90
io-203008	PS13R	110-240	82mA	LED13W	690lm	Φ180	Φ160	90
io-203009	PS18R	110-240	99mA	LED18W	900lm	Φ230	Φ210	90
io-203010	PS9S	110-240	99mA	LED9W	420lm	157*157	125*125	95
io-203011	PS13S	110-240	82mA	LED13W	690lm	185*185	150*150	95
io-203012	PS18S	110-240	99mA	LED18W	900lm	225*225	195*195	95
io-203013	PRO-PS14	220-240	70mA	LED14W	750lm	Φ145mm	Φ119mm	80
io-203014	PRO-PS18	220-240	90mA	LED18W	1050lm	Φ165mm	Φ139mm	80
io-203015	PRO-PS28	220-240	130mA	LED28W	1400lm	Φ195mm	Φ169mm	80
io-203016	ECO-PS218	220-240		CFL2*18W	2000lm	Φ230mm	Φ215mm	105
io-203017	ECO-PS226PL	220-240		PLC2*26W	3200lm	Φ230mm	Φ215mm	105