

Bulb Standard SMD LED

No UV or infrared radiation.

Mercury-Free.

Light-weight housing with excellent heat

Optimized heat fins with the artistic design.

Built-in LED current-control driver.

Constant light output.



C35S



G45S



A60S

Code	Model	Cap	W	Volt	CCT	LM	CRI	Lifetime	H(mm)	Diam.(mm)
io-401022	C35S-4W	E14	4W	220-240V	2700k	250	80	30000h	103	35
io-401023	G45S-4W	E27	4W	220-240V	2700k	250	80	30000h	87	46
io-401024	G45S-4W	E14	4W	220-240V	2700k	250	80	30000h	87	46
io-401025	A60S-7W	E27/B22	7W	100-240V	2700k	470	80	30000h	110	60

Bulb ECO SMD LED

No UV or infrared radiation.

Mercury-Free.

Light-weight housing with excellent heat

Optimized heat fins with the artistic design.

Built-in LED current-control driver.

Constant light output.



C38E



G45E



A55E

Code	Model	Cap	W	Volt	CCT	LM	CRI	Lifetime	H(mm)	Diam.(mm)
io-401026	C38E-2W	E14	2W	220-240V	3000k	136	80	30000h	111	38
io-401027	G45E-2W	E14	2W	220-240V	3000k	136	80	30000h	84	46
io-401028	G45E-2W	E27	2W	220-240V	3000k	136	80	30000h	79	46
io-401029	A55E-4W	E27/B22	4W	220-240V	3000k	250	80	30000h	110	55

Bulb Dimmable SMD LED

No UV or infrared radiation.

Mercury-Free.

Light-weight housing with excellent heat

Optimized heat fins with the artistic design.

Built-in LED current-control driver.

Constant light output.



C35D



G45D



A60D

Code	Model	Cap	W	Volt	CCT	LM	CRI	Lifetime	H(mm)	Diam.(mm)
io-401030	C35D-4.5W	E14	4.5W	220-240V	2700k	250	80	40000h	101	35
io-401031	G45D-4.5W	E14	4.5W	220-240V	2700k	250	80	40000h	87	46
io-401032	G45D-4.5W	E27	4.5W	220-240V	2700k	250	80	40000h	90	46
io-401033	A60D-12W	E27/B22	12W	220-240V	2700k	806	80	40000h	110	60

GX53 T30 LED

No UV or infrared radiation.

Mercury-Free.

Light-weight housing with excellent heat

Optimized heat fins with the artistic design.

Built-in LED current-control driver.

Constant light output.



GX53S



T30

Code	Model	Cap	W	Volt	CCT	LM	CRI	Lifetime	H(mm)	Diam.(mm)
io-401034	GX53S-4W	GX53	4W	220-240V	3000k	250	80	30000h	26	75
io-401035	T30-1.5W	E14	1.5W	220-240V	6000k	100	80	30000h	76	30
io-401036	T30-2W	E14	2W	100-240V	6000k	100	80	30000h	76	30