




HALOGEN ENERGY SAVER Classic C ErP/LCIE

- Average life:2 years(at approx 5 hours a day) •
- Light color: Warm white light •
- UV filter •
- Dimmable •



Code	Model	Voltage(V)	Watt(W)	Lumen (LM)	CCT (K)	Diam (mm)	Length(mm)	Life
io-402030	J78	220-240	80	1400	2900	12	78.3	1000
io-402031	J78	220-240	120	2300	2900	12	78.3	1000
io-402032	J78	220-240	200	4100	2900	12	78.3	1000
io-402033	J118	220-240	120	2300	2900	12	117.6	1000
io-402034	J118	220-240	160	3150	2900	12	117.6	1000
io-402035	J118	220-240	230	4780	2900	12	117.6	1000
io-402036	J118	220-240	400	8800	2900	12	117.6	1000

(normal version of J type serious is without UV)

Code	Model	Lamp holder	Volt(V)	Watt(W)	Lumen (LM)	Diam (mm)	Length(mm)	Life
io-402037	JTT	E27	220-240	60	840	48	117	1000
io-402038	JTT	E27	220-240	80	1500	48	117	1000
io-402039	JTT	E27	220-240	120	2500	48	117	1000

Code	Model	Lamp holder	Volt(V)	Watt(W)	Lumen (LM)	Diam (mm)	Length(mm)	Life
io-402040	JDD	E27	220-240	60	840	32	105	2000
io-402041	JDD	E27	220-240	80	1500	32	105	2000
io-402042	JDD	E27	220-240	120	2500	32	105	2000

Code	Model	Lamp holder	Volt(V)	Watt(W)	Lumen (LM)	CCT(K)	Diam (mm)	Length(mm)	Life
io-402043	JC	G4	12	8	100	2900	8	31	4000
io-402044	JC	G4	12	16	280	2900	8	31	4000
io-402045	JC	GY6.35	12	16	280	2900	10	40	4000
io-402046	JC	GY6.35	12	28	550	2900	10	40	4000
io-402047	JC	GY6.35	12	40	850	2900	10	40	4000

Code	Model	Lamp holder	Volt(V)	Watt(W)	Luminous intensity cd	Beam Angle(°)	Diam (mm)	Length(mm)	Life
io-402048	MR16	GU5.3	12	16	700	36	50	44	4000
io-402049	MR16	GU5.3	12	28	1300	36	50	44	4000
io-402050	MR16	GU5.3	12	40	1800	36	50	44	4000
io-402051	MR11	GU4	12	16	700	30	35	35	4000
io-402052	MR11	GU4	12	28	1500	30	35	35	4000

Code	Model	Volt(V)	Watt(W)	Luminous intensity cd	Beam Angle(°)	Diam (mm)	Length(mm)	Life
io-402053	AR111	12	40	20000	8	67	51	4000
io-402054	AR111	12	60	30000	8	67	51	4000
io-402055	AR111	12	80	48000	8	67	51	4000
io-402056	AR111	12	40	4000	24	67	51	4000
io-402057	AR111	12	60	5300	24	67	51	4000
io-402058	AR111	12	80	8500	24	67	51	4000

(base:argon-arc welding)

Code	Model	Volt(V)	Watt(W)	Luminous intensity cd	Beam Angle(°)	Diam (mm)	Length(mm)	Life
io-402059	GU10	220-240	28	500	30	51	55	2000
io-402060	GU10	220-240	40	900	30	51	55	2000

