

Flicker free, instant start and operation
 Low mercury ≤2mg
 With new Amalgam technology
 Quick start technology-fast run up time
 Lead free tube-better lumen maintenance over life of bulb
 Certification: CE, EMC, LVD, ROHS, ERP


Bulb

Code	Model	Volt (V)	Watt(W)	LM	Dia.	Max Length(mm)	Diameter(Φmm)	size per carton	qty/ctn	life
io-403001	BA28	220-240	13W	670	T2	115	60	60*31.5*15	50	8000
io-403002	BA28	220-240	15W	800	T2	115	60	65*34*15	50	8000
io-403003	BA28	220-240	20W	1050	T2	115	70	73*39*16.5	50	8000


Round

Code	Model	Volt (V)	Watt(W)	LM	Dia.	Max Length(mm)	Diameter(Φmm)	size per carton	qty/ctn	life
io-403004	BG39	220-240	5W	220	T2	90	45	48*48*12.5	100	8000
io-403005	BG39	220-240	7W	300	T2	90	45	48*48*12.5	100	8000
io-403006	BG39	220-240	9W	400	T2	96	60	63*33*24	100	8000


Candle

Code	Model	Volt (V)	Watt(W)	LM	Dia.	Max Length(mm)	Diameter(Φmm)	size per carton	qty/ctn	life
io-403007	BC18	220-240	5W	220	T2	107	39	41*41*14	100	8000
io-403008	BC18	220-240	7W	300	T2	107	39	41*41*14	100	8000
io-403009	BC18	220-240	9W	400	T2	117	39	41*41*15	100	8000


Full spiral

Code	Model	Volt (V)	Watt(W)	LM	Dia.	Max Length(mm)	Diameter(Φmm)	size per carton	qty/ctn	life
io-403010	FE23	220-240	5W	280	T3	100	40	49*49*12	100	8000
io-403011	FE23	220-240	8W	500	T3	107	40	49*49*12	100	8000
io-403012	FE23	220-240	12W	725	T3	113	40	49*49*14	100	8000
io-403013	FE23	220-240	15W	830	T3	110	50	49*49*14	100	8000


Full spiral

Code	Model	Volt (V)	Watt(W)	LM	Dia.	Max Length(mm)	Diameter(Φmm)	size per carton	qty/ctn	life
io-403014	FE24	220-240	20W	1200	T3	113	51	70*36*16	50	8000
io-403015	FE24	220-240	23W	1430	T3	121	51	70*36*16	50	8000


Full spiral

Code	Model	Volt (V)	Watt(W)	LM	Dia.	Max Length(mm)	Diameter(Φmm)	size per carton	qty/ctn	life
io-403016	BS70	220-240	30W	1950	T3	128	73	63*40.5*16	40	8000
io-403017	BS70	220-240	40W	2700	T3	144	73	63*40.5*18	40	8000


Globe

Code	Model	Volt (V)	Watt(W)	LM	Dia.	Max Length(mm)	Diameter(Φmm)	size per carton	qty/ctn	life
io-403018	BG28	220-240	20W	1180	T3	146	100	54*43.5*18	20	8000
io-403019	BG28	220-240	24W	1450	T3	146	100	54*43.5*18	20	8000
io-403020	BG28	220-240	27W	1670	T4	170	120	67*56*27.5	20	8000

