

### LED RGB Ribbon

Super flexible PCB board as base and Chip RGB LED as its luminous body. Two option:15pcs LED (12VDC)and 24pcs LED (24VDC). Easy installation with 3M tape on its back. Three LEDs(12VDC) or six LEDs(24VDC) can be cut according to the length requirement. When controlled by DMX512 or controlling system which is common positive, it can realize different kinds of effects,such as multi-color jumping,gradual color changing and etc.

LED Spacing:33mm(12VDC) or 20mm(24VDC)  
Width:11.7mm,5M/Reel  
Warranty: 24 months.



Single Side Connector for RGB Ribbon



Double Side Connector for RGB Ribbon



Flat Transparent Holder

| Code      | Model    | Description  | Input Voltage | Current (mA) | Consumption Watts | LED Qty    | Max Length of One Single Loop | Intensity (mcd)                           | Measurement | Waterproof or not |
|-----------|----------|--------------|---------------|--------------|-------------------|------------|-------------------------------|---|-------------|-------------------|
| io-503007 | R24RGB-S | RGB(5M/reel) | 24VDC         | 60mA*40      | 1.44W*40          | 24(RGB)*10 | 10M                           | R: > 350mcd<br>G: > 750mcd<br>B: > 200mcd | 5000*11.7mm | NO                |
| io-503008 | R15TGB-S | RGB(5M/reel) | 12VDC         | 60mA*50      | 0.72W*50          | 15(RGB)*10 | 5M                            | R: > 350mcd<br>G: > 750mcd<br>B: > 200mcd | 5000*11.7mm | NO                |

### LED RGB Crystal Ribbon IP65

Super flexible PCB board as base and Chip RGB LED as its luminous body. Two option:15pcs LED (12VDC)and 24pcs LED (24VDC).



The ribbon is flexible is flexible and easy-curved.Its stability,reliability and safety is enhanced greatly.Every three LEDs(12VDC) or six LEDs(24VDC) can be cut according to the length requirement. When controlled by DMX512 or other controlling system which is common positive,it can realize different kinds of effects,such as multi-color jumping,gradual color changing and etc.

LED Spacing:33mm(12VDC) or 20mm(24VDC)  
Width:14mm,5M/Reel  
Warranty: 24 months.



Extension Wire with White Waterproof Connector 100cm



Extension Wire with White Waterproof Connector 50cm



Flat Transparent Holder

| Code      | Model    | Description  | Input Voltage | Current (mA) | Consumption Watts | LED Qty    | Max Length of One Single Loop | Intensity (mcd)                           | Measurement | Waterproof or not |
|-----------|----------|--------------|---------------|--------------|-------------------|------------|-------------------------------|---|-------------|-------------------|
| io-503009 | R24RGB-S | RGB(5M/reel) | 24VDC         | 60mA*40      | 1.44W*40          | 24(RGB)*10 | 10M                           | R: > 350mcd<br>G: > 750mcd<br>B: > 200mcd | 5000*14mm   | IP65              |
| io-503010 | R15TGB-S | RGB(5M/reel) | 12VDC         | 60mA*50      | 0.72W*50          | 15(RGB)*10 | 5M                            | R: > 350mcd<br>G: > 750mcd<br>B: > 200mcd | 5000*14mm   | IP65              |