

LED SMD Bar

This product adopts 30pcs super bright SMD LED as its luminous body. These LEDs are evenly arranged on the PCB board. They are equipped with male and female connectors.

It is a slim linear lighting of variable application.

The luminous body is of very high intensity, large viewing angle, good quality and stability.

Consumption Watt: 2.4W/pc, LED Spacing: 16mm

Width: 8mm, 0.5m/peice

Warranty: 24 months



Mini Flat White Holder



Flat Transparent Holder

Code	Model	Description	Input Voltage	Current (mA)	Consumption Watts	LED Qty	Maximum Piece of One Single	Intensity (mcd)	Measurement	Waterproof or not
io-501013	B3528R-S	Red	12VDC	20mA*10	0.24W*10	3*10	12	> 400mcd*30	500*8mm	NO
io-501014	B3528Y-S	Yellow	12VDC	20mA*10	0.24W*10	3*10	12	> 750mcd*30	500*8mm	NO
io-501015	B3528B-S	Blue	12VDC	20mA*10	0.24W*10	3*10	12	> 400mcd*30	500*8mm	NO
io-501016	B3528G-S	Green	12VDC	20mA*10	0.24W*10	3*10	12	> 800mcd*30	500*8mm	NO
io-501017	B3528W-S	White	12VDC	20mA*10	0.24W*10	3*10	12	> 1500mcd*30	500*8mm	NO
io-501018	B3528WW-S	WarmWhite	12VDC	20mA*10	0.24W*10	3*10	12	> 1500mcd*30	500*8mm	NO

LED Waterproof SMD Bar IP54



Adopts super bright SMD 3528 LED as its luminous body, high intensity, large viewing angle, good quality and stability.

Elegant aluminum housing as its base and mini waterproof connector are matched.

Special epoxy gluing craft makes it achieves waterproof rate IP54.

LED Spacing: 16mm

Width: 10mm, 0.5M/peice

Warranty: 24 months



Extension Wire with Waterproof Connector 100cm



Extension Wire with Waterproof Connector 50cm



Waterproof SMD Bar Holder

Code	Model	Description	Input Voltage	Current (mA)	Consumption Watts	LED Qty	Maximum Piece of One Single	Intensity (mcd)	Measurement	Waterproof or not
io-501019	B3528R-SF	Red	12VDC	20mA*10	0.24W*10	3*10	12	>400mcd*30	520*10*5.2mm	IP54
io-501020	B3528Y-SF	Yellow	12VDC	20mA*10	0.24W*10	3*10	12	>750mcd*30	520*10*5.2mm	IP54
io-501021	B3528B-SF	Blue	12VDC	20mA*10	0.24W*10	3*10	12	>400mcd*30	520*10*5.2mm	IP54
io-501022	B3528G-SF	Green	12VDC	20mA*10	0.24W*10	3*10	12	>800mcd*30	520*10*5.2mm	IP54
io-501023	B3528W-SF	White	12VDC	20mA*10	0.24W*10	3*10	12	>1500mcd*30	520*10*5.2mm	IP54
io-501024	B3528WW-SF	WarmWhite	12VDC	20mA*10	0.24W*10	3*10	12	>1500mcd*30	520*10*5.2mm	IP54