


Electronic transformer

Rated Power: 60W
 Input Voltage: 220-240V AC50/60Hz
 Output Voltage: 11.6v-eff
 Power Factor: 0.99
 Ambient Temperature: max 50 °C
 Case Temperature: max 80 °C
 Abnormal Protection: Short circuit, overload & over-temperature protection
 Class: II
 RFI Suppression: According to EN55015




ET60A

Code	Item NO.	Rated load (W)	Efficiency (%)	Power loss (W)	Temp.range (°C)	Current(A)		L×W×H
						Input	Output	
io-601001	ET60A	20-60	95	< 3	-17-+50	0.27	4.9	108×32×22



Electronic transformer

Rated Power: 105W
 Input Voltage: 220-240V AC50/60Hz
 Output Voltage: 11.6v-eff
 Power Factor: 0.99
 Ambient Temperature: max 50 °C
 Case Temperature: max 80 °C
 Abnormal Protection: Short circuit, overload & over-temperature protection
 Class: II
 RFI Suppression: According to EN55015




ET105C-2

Code	Item NO.	Rated load (W)	Efficiency (%)	Power loss (W)	Temp.range (°C)	Current(A)		L×W×H
						Input	Output	
io-601002	ET105C-2	35-105	95	< 4	-17-+50	0.48	8.8	146×50×20

Electronic transformer

Rated Power: 150W
 Input Voltage: 220-240V AC50/60Hz
 Output Voltage: 11.6v-eff
 Power Factor: 0.99
 Ambient Temperature: max 50 °C
 Case Temperature: max 80 °C
 Abnormal Protection: Short circuit, overload & over-temperature protection
 Class: II
 RFI Suppression: According to EN55015



ET150B

Code	Item NO.	Rated load (W)	Efficiency (%)	Power loss (W)	Temp.range (°C)	Current(A)		L×W×H
						Input	Output	
io-601004	ET150B	50-150	95	< 4	-17-+50	0.69	12.7	180×46×32