


LED Driver Constant voltage



IP20 independant LED convertor, for indoor use.
 With output of DC 12V OR DC24V,Max.15W.
 Class II protection against electric shock following direct and indirect contact.

Protections:

- against overheating and short circuits.
- against open circuits.
- against overloads.

Auto restart after fault condition removal.

Comply with IEC EMC and safety requirement.


Input Voltage: 220-240V AC 50/60Hz

■ LC15-12VF/LC15-24VF

Code	Model	W	I out	V out	Ta° C	Tc° C	L×W×H(mm)	Weight(g)
io-602005	LC15-12VF	0.5-15W	1.25A	12V	45	75	118×43×22	85
io-602006	LC15-24VF	0.5-15W	0.63A	24V	45	75	118×43×22	85



LED Driver Constant voltage



IP20 independant LED convertor, for indoor use.
 DC 12V or DC 24V constant colltage output, Max.30W.
 Class II protection against electric shock following direct and indirect contact.
 High power factor[≥0.95].

Protections:

- against overheating and short circuits.
- against open circuits.
- against overloads.

Auto restart after fault condition removal.

Comply with IEC EMC and safety requirement.

Input Voltage: 220-240V AC 50/60Hz

■ LC30-12VF/LC30-24VF

Code	Model	W	I out	V out	Power factor	Ta° C	Tc° C	L×W×H(mm)	Weight(g)
io-602007	LC30-12VF	3-30W	2.5A	12V	≥0.95	45	75	150×40×30	155
io-602008	LC30-24VF	3-30W	1.25A	24V	≥0.95	45	75	150×40×30	155