

Flood Light CFL

MILTON

Plastic body
Clear PC diffuser.
Lamp: PLL fluorescent tube
Lamp Holder 2G11
Electric shock protection class: I
External light protection class: IP44
Rated voltage: 220-240V~ 50Hz
5M H07RN-F 3G1.50mm2 Cable+IP plug
2/3 IP sockets on back side
Included electronic ballast




ML324




ML436

ML24



Tempered glasses
Aluminium die-casting body
Color of body: Available
Area of Uses: Garden/Avenues/Structure
AC220V-240V,50Hz,R7s,24W,CFL

ML9



Tempered glasses
Aluminium die-casting body
Color of body: Available
Area of Uses: Garden/Avenues/Structure
AC220V-240V,50Hz,R7s,9W,CFL

Code	Model	Input Voltage	Lamp Power	Lumen	Packing Info
io-101049	ML324	220-240V	PLL 3*24W	4500	44.0*32.0*47.0cm/3pcs
io-101050	ML436	220-240V	PLL 4*36W	9000	46.0*38.5*54.0cm/3pcs
io-101051	ML24	220-240V	R7S 24W CFL	1400	57.5*29.5*33.5cm/24pcs
io-101052	ML9	220-240V	R7S 9W CFL	600	82.5*27.5*39cm/12pcs